



財團法人全國認證基金會
Taiwan Accreditation Foundation

Certificate of Accreditation

(Certificate No : L2586-240604)

This is to certify that

GONG-Hung Technology Co., Ltd.

GCH Technology Calibration Laboratory (Pressure)

No.1, Ln. 36, Wenfeng St., Fengshan Dist., Kaohsiung City 830, Taiwan (R.O.C.)

is accredited in respect of laboratory

Accreditation Criteria : ISO/IEC 17025:2017 ; CNS 17025:2018

Accreditation Number : 2586

Originally Accredited : May 03, 2012

Effective Period : August 26, 2024 to August 25, 2027

Accredited Scope : Calibration Field, see described in the Appendix



Scan to verify

Yi-Ling Chen

Yi-Ling Chen
President, Taiwan Accreditation Foundation
June 04, 2024

Accreditation Number : 2586

Laboratory Head : HUNG, Chuan-Hsi

Pressure/Vacuum

calibration items	working standard	calibration method	measurand level or range				measurement conditions /independent variable	smallest uncertainty	
	brand /model	document name /no.	minimum value	units	maximum value	units	explanation	value	units
KD1004 Pressure Gauge (on-site calibration included) Vacuum Gauge (on-site calibration included)	Digital Pressure Gauge (ASHCROFT /1000psi) Automated Pressure Calibrator (Additel/ADT761A)	In-house method: pressure gauge (on-site calibration included) calibration procedure (Document No.: GCH-SCP-P01) In-house method: vacuum gauge (on-site calibration included) calibration procedure (Document No.: GCH-SCP-P03)	0 (0)	kPa (kgf/cm ²)	1961 (20)	kPa (kgf/cm ²)	Digital Air Pressure Gauge	3.6 (0.036)	kPa (kgf/cm ²)
			0 (0)	kPa (kgf/cm ²)	1961 (20)	kPa (kgf/cm ²)	Dial Air Pressure Gauge	13 (0.13)	kPa (kgf/cm ²)
			0 (0)	kPa (kgf/cm ²)	5884 (60)	kPa (kgf/cm ²)	Digital Air Pressure Gauge	4.9 (0.05)	kPa (kgf/cm ²)
			0 (0)	kPa (kgf/cm ²)	5884 (60)	kPa (kgf/cm ²)	Dial Air Pressure Gauge	32 (0.32)	kPa (kgf/cm ²)
			0 (0)	kPa (mmHg)	-93.4 (-700)	kPa (mmHg)	Digital Vacuum Gauge	0.11 (0.8)	kPa (mmHg)
			0 (0)	kPa (mmHg)	-93.4 (-700)	kPa (mmHg)	Dial Vacuum Gauge	0.34 (2.5)	kPa (mmHg)
Approval Signatory: HUNG, Chuan-Hsi									



calibration items	working standard	calibration method	measurand level or range				measurement conditions /independent variable	smallest uncertainty	
	brand /model	document name /no.	minimum value	units	maximum value	units	explanation	value	units
KD1007 Differential Pressure Gauge (on-site calibration included)	Automated Pressure Calibrator (Additel /ADT761A)	In-house method: differential pressure gauge (on-site calibration included) calibration procedure (Document No.: GCH-SCP-P02)	0	Pa	250	Pa	Digital Differential Pressure Gauge	1.0	Pa
			0	Pa	250	Pa	Dial Differential Pressure Gauge	3.3	Pa
			0	Pa	5000	Pa	Digital Differential Pressure Gauge	4	Pa
			0	Pa	5000	Pa	Dial Differential Pressure Gauge	70	Pa
Approval Signatory: HUNG, Chuan-Hsi									

Note : Smallest uncertainty represents an expanded uncertainty using a coverage factor approximately 95 % level of confidence.
(Null Below)

